

Seccua MK7

Seccua MK7 is a water filtration system for easy installation under the sink. It filters pathogens and pollutants from drinking water and provides a pleasant taste and smell.



Reduces bacteria and germs up to 99.9 %



Reduces chlorine and chloramines



Reduces microplastics up to 99 % and plasticizers



Reduces PFOA/PFOS



Reduces lead up to 96 % and heavy metals



Reduces odor and improves water taste



Reduces rust and sediments



Quick and easy installation under the sink



Reduces pesticides



Quick and easy filter cartridge replacement



Reduces hormones and pharmaceutical residues



Waste less plastic, save money, and avoid bulky bottles



Dimensions and weight (complete filter)		
Height	29 cm / 11.4 in	
Width	7 cm / 2.8 in	
Depth	7 cm / 2.8 in	
Weight (dry)	700 g / 1.5 lb	

Filtration capacity	
Filtration	Three-stage filter (pre-filter, microfiltration membrane, activated carbon)
Rated flow	Up to 7 I/min / 1.85 gallons
Filtering rate	0.3 µm
Capacity	Up to 5,000 liters / up to 1,321 gallons
Filter replacement	Every 6 months or after 5,000 liters (1,321 gallons) filtration volume (whichever comes first).

Operating conditions	
Operating pressure	0.5-6.8 bar / 10-100 psi
Operating temperature	5-65 °C / 41-149 °F

The filter system is designed for treated drinking water (city water).

Retention	
Bacteria	>99.9 %
Microplastics	>99 %
Lead	>96 % (tested according to NSF 53)
Chlorine	Tested according to NSF 42
Hormones e.g. Estrogens	Tested according to NSF 401
Pharmaceutical residues e.g. lbuprofen, Naproxen	Tested according to NSF 401
Plasticizers e.g. Bisphenol A, Nonylphenol	Tested according to NSF 401

Reduces rust and pesticides as well as unpleasant taste and odor.

Approvals and standards	
Tested according to	NSF 42, 53, 372, 401

The products including packaging comply with REACH Regulation 1907/2006/EC. The products comply with the RoHS Directive 2011/65 and 2015/863 on the restriction of the use of certain hazardous substances. The materials in contact with drinking water either meet the requirements of the current positive list of the German Environmental Agency (UBS) or comply with the requirements of the UBA assessment basis KTW BWGL.

Connections and mounting	
Connections male	3/8" (in and out)
	Wall-mounted using screws or self-adhe-
Mounting	sive bracket, connection hoses, shut-off
	valve, and mounting material all included

Contact:

L +49 881 130 808-80

water-fluid-filtration.mann-hummel.com/drinkingwater/mk7.html

Manufacturer:

© Seccua GmbH, Dr.-Karl-Slevogt-Straße 3, 82362 Weilheim, Germany





